

# Intelli-flush

## The Intelligent Flush Timer

### How to set the time clock

1. Press and hold the **MODE** button until the 24hr clock flashes
2. Using the + or - buttons set the minutes and press **SET**
3. Using the + or - buttons set the hours and press **SET**
4. In the top of the screen there are 7 numbers which represent days of the week. 1 is Monday  
Using the + or - keys pick the day of the week it currently is and press **SET**

### How to set the timer settings

1. Press and hold the **MODE** button till the clock time is flashing. Once it is flashing press and hold the **MODE** button again until the *Start* time is flashing.
2. Using the + or - and **SET** buttons set the time that you wish the timer to start operating. Eg timer to operate from 6:00 in the morning.
3. Once this is done the display should say *End*. This is the time that you want the timer to switch off.  
Eg 18:00 - no flushing after 6pm at night.  
Using the + or - and SET buttons set the time.
4. The *On* time should now be displayed. This is the amount of time that you wish the solenoid to be open.  
Eg flush the urinal for 30secs.  
Using the + or - and **SET** buttons set the time. **Press the set button until you see "Off" flashing**
5. The *Off* time should now be displayed. This is the amount of time between flushes.  
Eg Do not flush for 2 hours.  
Using the + or - and **SET** buttons set the time.
6. Setting the days that the timer will operate on.  
At the top of the screen you will see that the *Number 1* will be flashing. This is to set the days that the system will operate. The + button will insert a box around the *number 1* which indicates it will flush on that day. The - button will remove the box.  
After selecting number 1 press the **SET** button to select the next days you want the unit to flush.
7. After setting number 7 and pressing the **SET** button the timer will then commence a test flush for the settings you have entered. The timer is now set and ready to use.

### Manual operation of the timer

To manually toggle the timer on or off simply press the **MODE** button once. The display should say *OFF*. To operate the timer simply press **MODE** again and the urinal will flush.

